





IP20

POWELED



POWELED P 12V 30W



POWELED P 12V 60W

Kanlux	Kanlux	PRI	SEC	Tc [°C]
POWELED P 12V 30W	26810	220-240V~; 50/60 Hz	12V DC max 2,5A max 30 W	max 80
POWELED P 12V 60W	26811		12V DC max 5A max 60 W	max 85



### GB

white, grey  
housing: plastic

Voltage stabilization 12V DC / Maximum permissible housing temperature: POWELED P 12V30W - 80°C, POWELED P 12V60W - 85°C / Built-in circuit protection / Built-in radio interference reduction systems / Short-circuit proof safety transformer

### DE

weiß, grau  
Gehäuse: Kunststoff

Spannungsstabilisierung 12V DC / Maximal zulässige Gehäusetemperatur von: POWELED P 12V30W - 80°C, POWELED P 12V60W - 85°C / Eingebauter Kurzschluss- und Überlastschutz / Eingegebute Systeme zur Reduktion der Funkstörungen / Sicherheitstransformator, kurzschlussfest

### FR

blanc, gris  
boîtier: plastique

stabilisation de tension 12V DC / température maximale admissible du boîtier de: POWELED P 12V 30W - 80°C, POWELED P 12V 60W - 85°C / protection contre les courts-circuits intégrée / systèmes de réduction des interférences radioélectriques intégrés / transformateur de sécurité résistant aux courts-circuits